

AGRIMAX RT 945 - Especificaciones técnicas



Description

AGRIMAX RT 945 se ha proyectado especialmente para los cultivos en hileras, ya que no daña los cultivos y protege la cosecha. Además, sus extraordinarias capacidades de auto-limpieza permiten pasar rápidamente del campo a la carretera, donde AGRIMAX RT 945 demuestra excelentes prestaciones. La carcasa robusta proporciona una excelente estabilidad, tracción excepcional y una durabilidad extraordinaria.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor

Version	STANDARD
Type	TL
Tyre Size	380/90 R 50 (14.9 R 50)
LI/SS	151 A8/B

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1954
Static Loaded Radius (mm)	906
Rolling Circumference (mm)	5900
SRI (mm)	925
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-001487
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8
50	1865	2415	2970	3210	3450	-
40	1865	2415	2970	3210	3450	-
30	2000	2590	3180	3440	3695	-
10	2745	3365	4090	4765	5020	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 14:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..