

## AGRIMAX SIRIO - Especificaciones técnicas



### Description

AGRIMAX SIRIO es un neumático para las altas velocidades (hasta 70 km/h) desarrollado por BKT para equipar los tractores de elevada potencia. El dibujo es perfecto para las aplicaciones de transporte y tratamiento del terreno. La elevada flexibilidad del flanco asegura una estabilidad, manutención y confort extraordinarios, mejorando la experiencia de conducir. Esta también disponible con tecnología IF permitiendo el transporte de cargas pesadas a baja presión. La carcasa reforzada y el número alto de cinturones garantizan una excelente tracción en el campo, mientras que la baja resistencia al rodamiento contribuye a un consumo menor de carburante.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor de alta potencia

|           |             |
|-----------|-------------|
| Version   | HIGH SPEED  |
| Type      | TL          |
| Tyre Size | 540/65 R 38 |
| LI/SS     | 153 D/150 E |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94044290       |
| Section Width (inch)         | 20.9           |
| Overall Diameter (inch)      | 65.6           |
| Static Loaded Radius (inch)  | 30.3           |
| Rolling Circumference (inch) | 198.8          |
| Rim Rec                      | W 16 L         |
| Rim Alt                      | W 18 L         |
| ECE                          | E4-106R-000816 |
| TRA Code                     | R1W            |

## Load capacity (lbs)

| mph / psi | 9    | 12   | 15   | 17   | 20   | 23    | 29    | 35    |
|-----------|------|------|------|------|------|-------|-------|-------|
| 45        | 3470 | 3990 | 4590 | 5170 | 5760 | 6360  | 6880  | 7390  |
| 40        | 3790 | 4350 | 4990 | 5630 | 6280 | 6920  | 7480  | 8050  |
| 30        | 3980 | 4570 | 5250 | 5920 | 6600 | 7270  | 7870  | 8450  |
| 25        | 4140 | 4760 | 5470 | 6170 | 6880 | 7580  | 8200  | 8820  |
| 15        | 4500 | 5160 | 5920 | 6690 | 7450 | 8210  | 8880  | 9550  |
| 5         | 5680 | 6530 | 7480 | 8450 | 9420 | 10380 | 11230 | 12070 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..