

AGRIMAX TURF RT 333 - Especificaciones técnicas



Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Maquina para la recogida de fruta •
Minitractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	240/70 R16
LI/SS	104 A8/B

Dimensions International Standard

Section Width (mm)	244
Overall Diameter (mm)	742
Static Loaded Radius (mm)	340
Rolling Circumference (mm)	2213
SRI (mm)	350
Rim Rec	W8
Rim Alt	W 8 L ; W 9
ECE	E11-106R-007531

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	425	490	560	630	705	775	850	900
40	425	490	560	630	705	775	850	900
30	455	525	600	680	755	830	910	965
10 LT	570	655	755	850	945	1045	1140	1210
10 HT	455	525	600	680	755	830	910	965

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 7:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..