

AGRIMAX TURF RT 333 - Especificaciones técnicas



Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Maquina para la recogida de fruta •
Minitractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	480/70 R 34
LI/SS	149 A8 / 149 B

Dimensions US Standard

Usa code	94075232
Section Width (inch)	19.3
Overall Diameter (inch)	62.2
Static Loaded Radius (inch)	28.5
Rolling Circumference (inch)	188.4
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-009042

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	3380	3870	4450	5020	5590	6170	6740	7170
25	3380	3870	4450	5020	5590	6170	6740	7170
20	3620	4150	4770	5380	5990	6610	7220	7680
5 LT	4520	5200	5970	6730	7500	8270	9030	9610
5 HT	3620	4150	4770	5380	5990	6610	7220	7680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 14:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..