

# AGRIMAX V-FLECTO - Especificaciones técnicas



## Description

AGRIMAX V-FLECTO es la respuesta de BKT a la demanda desafianta en clave de la tecnología y las prestaciones de los tractores de elevada potencia. Este neumático es perfecto para aplicaciones de tratamiento del terreno y de transporte gracias a una menor compactación del suelo. Con la innovadora tecnología VF, AGRIMAX V-FLECTO permite transportar cargas pesadas con una presión de inflado inferior en comparación con un neumático estándar o IF, alcanzando velocidades elevadas. Presenta l'Opción de Llanta Estrecha (NRO) que permite el montaje de llantas estándar. BKT ha diseñado este neumático con una geometría optimizada que incrementa el confort de conducción en el campo y por carretera reduciendo el consumo de carburante.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agricultura: Tractor de alta potencia

Version	STANDARD
Type	TL
Tyre Size	VF 600/60 R 28 NRO
LI/SS	157 D

## Dimensions US Standard

<b>Usa code</b>	94058495
<b>Section Width (inch)</b>	23.1
<b>Overall Diameter (inch)</b>	56.7
<b>Static Loaded Radius (inch)</b>	24.9
<b>Rolling Circumference (inch)</b>	166.5
<b>Rim Rec</b>	DW 20 B
<b>Rim Alt</b>	DW 18 L
<b>Narrow Rim option</b>	DW 18 L
<b>ECE</b>	E11-106R-004471
<b>TRA Code</b>	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
<b>45</b>	4540	5290	6030	6780	7520	8270
<b>from 40 to 25</b>	4990	5820	6640	7450	8270	9095
<b>20</b>	5090	5930	6770	7590	8430	9270
<b>12</b>	5190	6050	6900	7750	8600	9460
<b>5</b>	5490	6390	7300	8190	9090	10000
<b>*Upto 5 Cyc with front loader</b>	6990	8150	9280	10430	11570	12730
<b>5 HT</b>	5090	5930	6770	7590	8430	9270

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..