

AGRIMAX V-FLECTO - Especificaciones técnicas



Description

AGRIMAX V-FLECTO es la respuesta de BKT a la demanda desafianta en clave de la tecnología y las prestaciones de los tractores de elevada potencia. Este neumático es perfecto para aplicaciones de tratamiento del terreno y de transporte gracias a una menor compactación del suelo. Con la innovadora tecnología VF, AGRIMAX V-FLECTO permite transportar cargas pesadas con una presión de inflado inferior en comparación con un neumático estándar o IF, alcanzando velocidades elevadas. Presenta l'Opción de Llanta Estrecha (NRO) que permite el montaje de llantas estándar. BKT ha diseñado este neumático con una geometría optimizada que incrementa el confort de conducción en el campo y por carretera reduciendo el consumo de carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor de alta potencia

Version	STANDARD
Type	TL
Tyre Size	VF 600/65 R 34 NRO
LI/SS	169 D

Dimensions US Standard

Usa code	94070275
Section Width (inch)	23.5
Overall Diameter (inch)	64.7
Static Loaded Radius (inch)	28.8
Rolling Circumference (inch)	195
Rim Rec	DW 21 B
Rim Alt	DW 20 B
Narrow Rim option	DW 18 L
ECE	E11-106R-007603
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	5360	6170	7100	7910	8840	9660	10820	11630
From 40 to 25	5890	6780	7800	8700	9720	10610	11890	12790
20	6010	6910	7960	8870	9920	10820	12140	13040
12	6120	7050	8110	9050	10110	11030	12370	13290
5	6470	7460	8590	9570	10690	11680	13080	14060
*Upto 5 Cyc with front loader	8240	9490	10920	12180	13610	14860	16650	17900
5 HT	6010	6910	7960	8870	9920	10820	12140	13040

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 17:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..