

AIROMAX AM 543 - Especificaciones técnicas



Description

AIROMAX AM 543 es el neumático ideal para las grúas que se utilizan en el sector de la construcción. Este neumático presenta una excelente tracción, así como una elevada estabilidad. Visto que los neumáticos para grúas están sometidos a solicitaciones y condiciones de empleo extremas, AIROMAX AM 543 ha sido proyectado para proporcionar una óptima resistencia al calor. Además, es idóneo para todas las operaciones en las que se requiere un elevado nivel de maniobrabilidad.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Grúa móvil

Version	STANDARD
Type	TL
Tyre Size	445/95 R 25 (16.00 R 25)
LI/SS	177 E

Dimensions US Standard

Usa code	94036660
Overall Width (inch)	17.1
Overall Diameter (inch)	58.3
Static Loaded Radius (inch)	26.4
Rolling Circumference (inch)	177.2
Rim Rec	11.25/2.0
Rim Alt	11.00/1.7 CR ; 11.00/1.7CRL

Load capacity (lbs)

mph / psi	131
20	20900
25	19800
30	18700
35	18200
43	16100
50	13200
55	11400
62	9650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 6:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..