

AS 511 - Especificaciones técnicas



Description

AS 511 es ideal para máquinas agrícolas que se utilizan en las superficies herbosas. La robusta carcasa y la mezcla de la banda de rodadura particularmente resistente a los cortes garantizan una óptima estabilidad y un rendimiento optimizado. AS 511 ofrece una tracción excelente y minimiza la compactación del suelo

UM

International Standard

Construction



RADIAL

Machinery

Agricultura: Maquinaria agrícola

Version	STANDARD
Type	TL
Tyre Size	33 X 15.50 R 15
LI/SS	126 B

Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	840
Static Loaded Radius (mm)	375
Rolling Circumference (mm)	2533
SRI (mm)	400
Rim Rec	13 LB
ECE	E11-106R-0010516

Load capacity (Kg)

km/h / bar	2.8
50	1700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 13:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..