

AT 108 - Especificaciones técnicas

Description

AT 108 es un neumático todo terreno para vehículos ATV. El dibujo de la banda de rodadura asegura un confort excelente y prestaciones dentro y fuera de las carreteras.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Vehículo ATV



Version	STANDARD
Type	TL
Tyre Size	AT 23 X 8 - 11

Dimensions International Standard

Ply Rating	6
Section Width (mm)	191
Overall Diameter (mm)	594
Rim Rec	6.5 AT
Rim Alt	6.0 AT

Load capacity (Kg)

km/h / bar	0.45
80	132

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 22:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..