

AT 111 HD - Ficha técnica



Description

AT 111 HD es idóneo para las aplicaciones deportivas todo terreno con vehículos ATV. La profundidad incrementada y el fuerte espesor de los flancos ofrecen una extrema adherencia y control de frenado, junto a una excelente tracción y control con altas velocidades y en las maniobras de sobreviraje. AT 111 HD asegura un largo ciclo de vida del neumático.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Vehículo ATV

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
AT 20 X 11 - 9	STANDARD	94026883	43 J	6	9.0 AT	8.5 AT	10.8	20.3	TL	E4-75R-0006326
AT 22 X 11 - 9	STANDARD	94026890		6	9.0 AT	8.5 AT	11	22	TL	E4-75R-0006332
AT 20 X 11 - 10	STANDARD	94027002		6	9.0 AT	8.5 AT	11	19.9	TL	E4-75R-0006327
AT 21 X 7 - 10	STANDARD	94027019	30 J	6	5.5 AT	6.0 AT	7	21	TL	E4-75R-0006329
AT 22 X 11 - 10	STANDARD	94027026		6	9.0 AT	8.5 AT	11	22	TL	E4-75R-0006333
AT 22 X 7 - 10	STANDARD	94027033		6	5.5 AT	6.0 AT	6.9	22	TL	E4-75R-0006331
AT 23 X 7 - 10	STANDARD	94027040		6	5.5 AT	6.0 AT	6.9	23	TL	E4-75R-0006335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 7:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..