

AT 111 - Especificaciones técnicas

Description

AT 111 es idóneo para las aplicaciones deportivas todo terreno con vehículos ATV. Para los usuarios que necesiten una mayor durabilidad, hay disponible una versión "HD" con una banda de rodadura profunda.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Vehículo ATV



Version	STANDARD
Type	TL
Tyre Size	AT 22 X 11 - 8

Dimensions US Standard

Usa code	94001088
Ply Rating	6
Section Width (inch)	11.1
Overall Diameter (inch)	22
Rim Rec	9.0 AT
Rim Alt	8.5 AT
ECE	E4-75R-0004984-01

Load capacity (lbs)

mph / psi	7
62	395

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 5:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..