

AT 316 - Especificaciones técnicas



Description

AT 316 es idóneo para los tractores compactos utilizados en los servicios realizados para la municipalidad y el mantenimiento. Su particular dibujo de la banda de rodadura asegura una excelente tracción sin comprometer la protección del terreno, siendo ésta una característica esencial para este tipo de aplicación. El neumático AT 316 también está disponible en la versión "aramid belted", con cinturones de aramida, que proporcionan una mayor resistencia a la perforación.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricultura: Tractor compacto

Version	ARAMID BELTED
Type	TL
Tyre Size	24 X 12.00 - 12

Dimensions US Standard

Usa code	94001217
Ply Rating	6
Section Width (inch)	12.4
Overall Diameter (inch)	24
Static Loaded Radius (inch)	10.7
Rolling Circumference (inch)	69.6
Rim Rec	10.50 I - 55 ; I - 70 ; I - 90

Load capacity (lbs)

mph / psi	32
10	2270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 8:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..