

## AT 625 - Especificaciones técnicas



### Description

El neumático AT 625 está diseñado para retroexcavadoras y cargadoras compactas, sobresaliendo en todas las operaciones agrícolas, de excavación y carga. También es una opción ideal para la cosecha de caña de azúcar, ya que ofrece la confiabilidad necesaria para mantener la productividad durante toda la temporada. Gracias a la banda de rodadura extraprofunda, el AT 625 garantiza una mayor resistencia a pinchazos y durabilidad para afrontar condiciones adversas con confianza. Este neumático ofrece una tracción y estabilidad excepcionales, combinadas con una mayor resistencia a los cortes y las astillas, lo que lo convierte en un compañero duradero y confiable para sus tareas agrícolas.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Cosechadora

Industrial: Cargadora retroexcavadora • Cargadora compacta

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 14.9 - 24 |
| LI/SS     | 145 A8    |

# Dimensions International Standard

|                            |                         |
|----------------------------|-------------------------|
| Ply Rating                 | 12                      |
| Section Width (mm)         | 400                     |
| Overall Diameter (mm)      | 1265                    |
| Static Loaded Radius (mm)  | 575                     |
| Rolling Circumference (mm) | 3800                    |
| Rim Rec                    | DW 13                   |
| Rim Alt                    | DW 11 ; DW 12 ; DW 13 L |
| TRA Code                   | R4                      |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 2.90 |
| 40         | 2900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 5:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..