

AW 09 - Especificaciones técnicas



Description

AW 09 ha sido desarrollado para la maquinaria agrícola, las empacadoras de heno y los remolques que se utilizan en los trabajos del campo, en la cosecha de heno y en el transporte. Es idóneo para utilizarlo en la agricultura moderna tanto por carretera como fuera de la carretera. Su carcasa reforzada garantiza elevada capacidad de carga y una vida operativa más larga. AW 09 está realizado con una mezcla de la banda de rodadura resistente a las perforaciones que fornece una excelente resistencia a los rastros insidiosos.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora •
Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	320/80 - 15.3
LI/SS DRIVE WHEEL	133 A8
LI/SS FREE ROLLING	145 A8

Dimensions International Standard

Section Width (mm)	309
Overall Diameter (mm)	901
Static Loaded Radius (mm)	392
Rolling Circumference (mm)	2640
Rim Rec	9.00
ECE	E4-106R-000378

Load capacity (Kg)

km/h / bar	4.00
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900
10 DW	2885
25 DW	2450
30 DW	2305
40 DW	2060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 13:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..