

AW 708 - Especificaciones técnicas

Description

AW 708 ha sido desarrollado para trabajar en el campo y en las aplicaciones de transporte y recogida de heno con maquinaria agrícola, remolques y empacadoras de paja. AW 708 está disponible en una versión realizada con una mezcla especial resistente a los cortes y los desgarres.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricultura: Empacadora de heno • Maquinaria agrícola •
Remolque
Industrial: Remolque



Version	STANDARD
Type	TT
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	145 A8

Dimensions US Standard

Usa code	94010301
Ply Rating	14
Section Width (inch)	15.9
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	100.9
Rim Rec	AG 13.00
ECE	E4-106R-002712

Load capacity (lbs)

mph / psi	52
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 2:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..