

## AW 711 - Especificaciones técnicas



### Description

AW 711 es un neumático radial para maquinaria agrícola específicamente proyectado para la agricultura moderna y adecuado para aplicaciones de transporte, de recogida de heno y los trabajos del terreno. Gracias a la mezcla especial de la banda de rodamiento, AW 711 asegura un amplio ciclo de vida del producto, tanto cuando se utiliza en superficies blandas como duras. La baja resistencia al rodamiento durante el desplazamiento por carretera garantiza ahorros significativos en el consumo de carburante. Gracias a la tecnología VF, AW 711 ofrece una capacidad de carga elevada a bajas presiones.

### UM

US Standard

### Construction



RADIAL

### Machinery

Agricultura: Cosechadora • Maquinaria agrícola

|           |                   |
|-----------|-------------------|
| Version   | STUBBLE RESISTANT |
| Type      | TL                |
| Tyre Size | 380/55 R 16.5     |
| LI/SS     | 150 A8/B          |

Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94044757       |
| Section Width (inch)         | 14.2           |
| Overall Diameter (inch)      | 32.7           |
| Static Loaded Radius (inch)  | 14.6           |
| Rolling Circumference (inch) | 98.4           |
| Rim Rec                      | 12             |
| Rim Alt                      | 11.75          |
| ECE                          | E4-106R-001393 |

Load capacity (lbs)

|           |      |      |      |      |      |      |      |      |      |       |
|-----------|------|------|------|------|------|------|------|------|------|-------|
| mph / psi | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   | 73    |
| 30        | 2220 | 2890 | 3550 | 4070 | 4730 | 5400 | 5760 | 6360 | 6940 | 7400  |
| 25        | 2220 | 2890 | 3550 | 4070 | 4730 | 5400 | 5760 | 6360 | 6940 | 7400  |
| 20        | 2490 | 3230 | 3980 | 4560 | 5300 | 6050 | 6460 | 7120 | 7780 | 8280  |
| 15        | 2650 | 3440 | 4230 | 4840 | 5630 | 6430 | 6870 | 7570 | 8280 | 8800  |
| 10        | 2800 | 3640 | 4480 | 5130 | 5960 | 6800 | 7270 | 8010 | 8760 | 9310  |
| 5         | 3110 | 4030 | 4970 | 5690 | 6620 | 7550 | 8070 | 8900 | 9720 | 10340 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 5:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..