

AW 711 - Especificaciones técnicas



Description

AW 711 es un neumático radial para maquinaria agrícola específicamente proyectado para la agricultura moderna y adecuado para aplicaciones de transporte, de recogida de heno y los trabajos del terreno. Gracias a la mezcla especial de la banda de rodamiento, AW 711 asegura un amplio ciclo de vida del producto, tanto cuando se utiliza en superficies blandas como duras. La baja resistencia al rodamiento durante el desplazamiento por carretera garantiza ahorros significativos en el consumo de carburante. Gracias a la tecnología VF, AW 711 ofrece una capacidad de carga elevada a bajas presiones.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cosechadora • Maquinaria agrícola

Version	STEEL BELTED
Type	TL
Tyre Size	VF 410/50 R 16.5
LI/SS	153 B

Dimensions International Standard

Section Width (mm)	410
Overall Diameter (mm)	835
Static Loaded Radius (mm)	350
Rolling Circumference (mm)	2513
SRI (mm)	400
Rim Rec	AG 11.75
ECE	E11-106R-005024

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.6
From 10 to 50	1025	1345	1630	1890	2175	2465	2655	2910	3195	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..