

AW 711 - Especificaciones técnicas



Description

AW 711 es un neumático radial para maquinaria agrícola específicamente proyectado para la agricultura moderna y adecuado para aplicaciones de transporte, de recogida de heno y los trabajos del terreno. Gracias a la mezcla especial de la banda de rodamiento, AW 711 asegura un amplio ciclo de vida del producto, tanto cuando se utiliza en superficies blandas como duras. La baja resistencia al rodamiento durante el desplazamiento por carretera garantiza ahorros significativos en el consumo de carburante. Gracias a la tecnología VF, AW 711 ofrece una capacidad de carga elevada a bajas presiones.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Cosechadora • Maquinaria agrícola

Version	STEEL BELTED
Type	TL
Tyre Size	VF 480/45 R 17
LI/SS	167 A8/B

Dimensions US Standard

Usa code	94051434
Section Width (inch)	19.3
Overall Diameter (inch)	34.1
Static Loaded Radius (inch)	14.3
Rolling Circumference (inch)	104.1
Rim Rec	16.00
ECE	E4-106R-002652

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	73
From 5 to 30 mph	3490	4450	5410	6130	7100	8060	8900	9730	10700	12010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 2:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..