

AW 726 - Especificaciones técnicas



Description

AW 726 ha sido particularmente desarrollado para remolques en las aplicaciones de transporte. Este neumático es idóneo para utilizarlo tanto por la carretera como fuera de la carretera. AW 726 asegura óptimas prestaciones en la carretera y una excelente auto-limpieza. El dibujo con bloques asegura un amplio ciclo de vida del producto.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Remolque

Version	STANDARD
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	300
Overall Diameter (mm)	855
Static Loaded Radius (mm)	363
Rolling Circumference (mm)	2531
Rim Rec	9.00
ECE	E11-106R-005264

Load capacity (Kg)

km/h / bar	4.80
10 FR	3400
25 FR	2890
30 FR	2720
40 FR	2430
10 DW	2380
25 DW	2025
30 DW	1905
40 DW	1700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 6:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..