

## BK 308 - Ficha técnica



### Description

BK 308 ha sido particularmente proyectado para los remolques y los tractores compactos. Este neumático se distingue por su excelente tracción en todas las superficies y los elementos intermedios (tie bar) entre los tacos de la banda de rodadura para reducir el efecto de las grietas de fatiga en la banda de rodadura. La robusta carcasa realizada con una mezcla especial de la banda de rodadura, ofrece una excelente duración y una óptima resistencia contra los pinchazos, asegurando una vida operativa más amplia.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agricultura: Tractor compacto • Remolque

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
6.50 - 20	STANDARD	112 A6	10	5.50 F	4.00 E ; 5.00 F	190	865	TT	E11-106R-003563

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 1:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..