

## BK 4040 - Especificaciones técnicas



### Description

BK 4040 está principalmente proyectado para remolques agrícolas en las aplicaciones de transporte. Su robusta carcasa proporciona una elevada capacidad de carga y una durabilidad superior.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Remolque

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16

# Dimensions International Standard

Ply Rating	10
Section Width (mm)	182
Overall Diameter (mm)	740
Rim Rec	4.50 E
ECE	E11-106R-005299

## Load capacity (Kg)

km/h / bar	4.10
30	1010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 2:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..