

BK 826 - Especificaciones técnicas



Description

El neumático BK 826 está diseñado por expertos para remolques en aplicaciones de transporte, ofreciendo una durabilidad y prestaciones inigualables. La versión 'Harvester Special' está diseñada específicamente para la cosecha, lo que garantiza una fiabilidad óptima en el campo. Este neumático diagonal cuenta con una carcasa reforzada, que ofrece una capacidad de carga excepcional para satisfacer las demandas de las tareas pesadas. Además, la BK 826 está disponible en una variante "Industrial", diseñada con una resistencia superior al corte y a las virutas, lo que la convierte en una opción ideal para las retroexcavadoras en condiciones difíciles.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Cosechadora • Remolque
Industrial: Cargadora retroexcavadora • Remolque

Version	INDUSTRIAL
Type	TT
Tyre Size	8.25 - 16

Dimensions US Standard

Usa code	94048274
Ply Rating	16
Section Width (inch)	9.4
Overall Diameter (inch)	34
Rim Rec	6.50 H
Rim Alt	6.00 G

Load capacity (lbs)

mph / psi	122
25 LS	4695
25 LD	4445

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..