

COMMANDER (R) - Especificaciones técnicas



Description

COMMANDER (R) es un neumático agricultura que se caracteriza por una banda de rodadura profunda con una base fuerte de los tacos, asegurando un ciclo de vida del neumático más amplio. El especial dibujo de los tacos con dos angulaciones garantiza una excelente tracción en el campo así como elevadas propiedades de auto-limpieza. La robusta carcasa está realizada con una mezcla particularmente resistente a cualquier tipo de corte, aportando una mejor resistencia a los pinchazos y asegurando una capacidad de carga elevada. COMMANDER (R) es el neumático perfecto para los trabajos del campo y las operaciones de transporte y de recogida.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Cosechadora • Tractor

Version	STANDARD
Type	TT
Tyre Size	18.4 - 30
LI/SS	145 A8

Dimensions US Standard

Usa code	94051502
Ply Rating	14
TMPH	1
Section Width (inch)	18.6
Overall Diameter (inch)	61.6
Static Loaded Radius (inch)	28.9
Rolling Circumference (inch)	190.3
Rim Rec	W 16 L
ECE	E11-106R-004525
TRA Code	R1

Load capacity (lbs)

mph / psi	38
25	6780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..