

CON STAR - Especificaciones técnicas



Description

CON STAR es particularmente idóneo para las palas compactas y telescópicas que se utilizan en las aplicaciones agro-industriales de levantamiento y carga. El neumático se caracteriza por una excelente tracción combinada a una extraordinaria estabilidad vertical y horizontal. CON STAR ha sido realizado con una mezcla especialmente resistente a cualquier tipo de corte, prolongando el ciclo de vida del neumático.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricultura: Cargadora compacta • Elevador telescópico
Industrial: Cargadora compacta • Elevador telescópico

Version	INDUSTRIAL
Type	TL
Tyre Size	340/80 - 20 (12.5/80 - 20)
LI/SS	144 A8

Dimensions US Standard

Usa code	94051311
Section Width (inch)	13.8
Overall Diameter (inch)	41.9
Static Loaded Radius (inch)	19.3
Rolling Circumference (inch)	128.8
Rim Rec	11
Rim Alt	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11
ECE	E11-106R-003021

Load capacity (lbs)

mph / psi	58
25	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 0:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..