

CON TRAILER - Ficha técnica



Description

CON TRAILER es un neumático particularmente idóneo para los remolques que se usan en las aplicaciones portuarias, ideal tanto para la carretera como fuera de la carretera. Su robusta construcción se traduce en una elevada capacidad de carga, mientras que la banda de rodadura extra profunda permite un mejor kilometraje.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Remolque

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
10.00 - 20	PORT INDUSTRIAL	94050369	18	7.5	7.0 ; 8.0	11.3	42.5	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 1:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..