

CONTAINER KING - Especificaciones técnicas



Description

CONTAINER KING ha sido particularmente proyectado para todas las aplicaciones de transporte intermodal y logísticas con las grúas cargadoras de contenedores. Este extraordinario neumático ha sido realizado con una mezcla de la banda de rodadura extremadamente resistente al desgaste, reduciendo las grietas en la banda de rodadura. CONTAINER KING asegura un ciclo de vida prolongado, así como una excepcional estabilidad en la modalidad de elevación.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Grúa Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 33

Dimensions US Standard

Usa code	94064526
Ply Rating	40
Overall Width (inch)	20.1
Overall Diameter (inch)	74.6
Static Loaded Radius (inch)	33.5
Rolling Circumference (inch)	229.1
Rim Rec	13.00/2.5
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	59520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 6:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..