

CRANE SPECIAL - Especificaciones técnicas



Description

CRANE SPECIAL es idóneos para las grúas móviles Pick & Carry utilizadas en terrenos difíciles. El neumático ha sido realizado con una mezcla especial que aporta una elevada estabilidad y durabilidad.

UM

US Standard

Construction



Machinery

Industrial: Grúa móvil

Version	STANDARD
Туре	π
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94043934
Ply Rating	24
Overall Width (inch)	14.8
Overall Diameter (inch)	53.9
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	159.4
Rim Rec	10.00 W
TRA Code	E3

Load capacity (lbs)

mph / psi	83
30	11400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 15:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..