

DESERT KING - Ficha técnica



Description

DESERT KING es más adecuado para tierra suelta, terrenos arenosos y aplicaciones de pavimentación con camiones del desierto. El diseño optimizado de la banda de rodadura ofrece una excelente flotación y estabilidad direccional. Su fuerte carcasa de nylon y su talón de alta resistencia se han desarrollado especialmente para operaciones con presión baja. DESERT KING también proporciona una alta resistencia a pinchazos y una mayor vida útil del neumático.

UM

International Standard

Construction

✦ BIAS

Machinery

OTR: Camión del desierto

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	Tread Depth
18.00 - 25 DT	STANDARD	E7	16	10.00/1.5		470	1535	635	4405	TL	16
21.00 - 25 DT	STANDARD	E7	16	15.00/3.0		570	1660	708	4906	TL	18
29.5 - 25 DT	STANDARD	E7	28	25.00/3.5		770	1822	786	5392	TL	20

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..