

## EARTHMAX SR 22 - Especificaciones técnicas



### Description

EARTHMAX SR 22 (G-2/L-2) es un neumático radial **All Steel** particularmente proyectado para las motoniveladoras y cargadoras que operan en condiciones invernales extremas en la nieve o en el hielo. Los operadores apreciarán la excelente tracción y la extraordinaria estabilidad garantizadas por el dibujo de la banda de rodadura ancho y no-direccional.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Buldócer • Motoniveladora • Pala cargadora

OTR: Buldócer • Motoniveladora • Pala cargadora

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 17.5 R 25              |
| LI/SS     | 167 B/182 A2           |

## Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94052387  |
| Overall Width (inch)         | 17.8      |
| Overall Diameter (inch)      | 53.1      |
| Static Loaded Radius (inch)  | 23.2      |
| Rolling Circumference (inch) | 155.5     |
| Rim Rec                      | 14.00/1.5 |
| Star Rating                  | **        |
| TRA Code                     | E2/L2     |
| Tread Depth                  | 35        |

## Load capacity (lbs)

| mph / psi | 58   | 62    | 65    | 69    | 73    | 76    | 80    | 83    | 87    | 91    | 94    |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 9650 | 10200 | 10500 | 11000 | 11400 | 12000 | --    | --    | --    | --    | --    |
| 5         | --   | --    | --    | --    | --    | 16100 | 16500 | 17100 | 17600 | 18200 | 18700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..