

EARTHMAX SR 31 - Especificaciones técnicas



Description

EARTHMAX SR 31 es un neumático radial All Steel diseñado específicamente para volquetes articulados y cargadoras de ruedas. Sus múltiples cinturones de acero ofrecen una resistencia y estabilidad extraordinarias, mientras que el patrón de bloques rígido no direccional es sinónimo de excelencia en tracción y maniobrabilidad, incluso en terrenos embarrados. Además de destacar por su comodidad de conducción, que es excelente durante operaciones de "carga y transporte" sobre superficies duras mejoradas, EARTHMAX SR 31 presenta un compuesto de banda de rodadura que lo hace especialmente resistente a los cortes y al calor. La estructura de carcasa radial también ofrece una menor resistencia al rodamiento, con un ahorro de combustible significativo.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Buldócer • Pala cargadora

OTR: Volquete articulado • Buldócer • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	216 A2

Dimensions US Standard

Usa code	94054398
Overall Width (inch)	30.1
Overall Diameter (inch)	73.3
Static Loaded Radius (inch)	32.2
Rolling Circumference (inch)	218.7
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	L3
Tread Depth	53

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	41900	43000	44100	45400	46700	49400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 4:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..