

EARTHMAX SR 32 - Especificaciones técnicas



Description

EARTHMAX SR 32 es un neumático radial de base ancha no direccional para las mototraíllas. Este neumático se caracteriza por una robusta carcasa All Steel y una mezcla específicamente formulada que aseguran una excelente resistencia a los cortes y las laceraciones así como durabilidad. Otras ventajas son tracción y flotación excepcionales también en condiciones de trabajo pesadas.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Mototraílla

Version	STANDARD COMPOUND
Type	TL
Tyre Size	40.5/75 R 39
LI/SS	225 B

Dimensions International Standard

TKPH	689
Overall Width (mm)	985
Overall Diameter (mm)	2610
Static Loaded Radius (mm)	1164
Rolling Circumference (mm)	7924
Rim Rec	32.00/4.5
Star Rating	**
TRA Code	E3
Tread Depth	59

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	23600	25000	25750	27250	28000	29000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 14:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..