

EARTHMAX SR 331 - Especificaciones técnicas



Description

EARTHMAX SR 331 es el nuevo neumático BKT con patrón de banda de rodadura multibloque especialmente diseñado y concebido para camiones multiuso y vehículos de respuesta ante emergencias. El exclusivo patrón de la banda de rodadura es esencial para maximizar el contacto con el suelo y, por tanto, garantiza una excelente maniobrabilidad y confort en cualquier condición. Este neumático no direccional tiene unas propiedades de autolimpieza extraordinarias. BKT ha diseñado EARTHMAX SR 331 para que destaque en flotación y tracción, requisitos esenciales para operar eficazmente en suelos blandos, arenosos y embarrados. La mayor durabilidad está garantizada por su fuerte carcasa All Steel y el paquete de correas, que también proporcionan una extraordinaria resistencia a desgarros y pinchazos.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	24 R 21
LI/SS	176 G

Dimensions US Standard

Usa code	94067671
Ply Rating	16
Overall Width (inch)	23.9
Overall Diameter (inch)	54.4
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	165.1
Rim Rec	18.00
ECE	E11-54R-0019350
Tread Depth	30

Load capacity (lbs)

mph / psi	85
56	15700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 8:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..