

## EARTHMAX SR 35 - Ficha técnica



### Description

Earthmax SR 35 es un neumático radial All Steel de bajo perfil, particularmente proyectado para dúmpers articulados y cargadoras de ruedas. Es ideal para las operaciones que requieren una excelente tracción y flotación. Earthmax SR 35 asegura una excelente tracción y estabilidad. Gracias a la robusta carcasa con cinturones de acero, el neumático garantiza una extraordinaria durabilidad y resistencia contra desgarres y pinchazos.

### UM

International Standard

### Construction



RADIAL

### Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora

| SIZE                        | Version                | TRA Code | Star R | LI/SS        | RIM REC    | RIM ALT               | OW  | OD   | SLR | RC   | Type | Tread Depth | TKPH |
|-----------------------------|------------------------|----------|--------|--------------|------------|-----------------------|-----|------|-----|------|------|-------------|------|
| 650/65 R 25<br>(25/65 R 25) | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 180 B/193 A2 | 19.50/2.5  |                       | 635 | 1498 | 669 | 4493 | TL   | 39          | 202  |
| 650/65 R 25<br>(25/65 R 25) | CUT RESISTANT COMPOUND | L3       | *      | 193 A2       | 19.50/2.5  |                       | 635 | 1498 | 669 | 4493 | TL   | 39          |      |
| 650/65 R 25<br>(25/65 R 25) | CUT RESISTANT COMPOUND | E3       | **     | 180 B        | 19.50/2.5  |                       | 635 | 1498 | 669 | 4493 | TL   | 39          | 202  |
| 750/65 R 25<br>(30/65 R 25) | CUT RESISTANT COMPOUND | E3       | **     | 190 B        | 24.00/3.0  | 22.00/3.0,25.00/3.0   | 740 | 1601 | 715 | 4802 | TL   | 42          | 223  |
| 750/65 R 25<br>(30/65 R 25) | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 190 B/202 A2 | 24.00/3.0  | 22.00/3.0 ; 25.00/3.0 | 740 | 1601 | 715 | 4802 | TL   | 42          | 223  |
| 750/65 R 25<br>(30/65 R 25) | CUT RESISTANT COMPOUND | L3       | **     | 209 A2       | 24.00/3.0  | 22.00/3.0,25.00/3.0   | 740 | 1601 | 715 | 4802 | TL   | 42          |      |
| 775/65 R 29                 | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 195 B/206 A2 | 24.00/3.5  | 24.00/3.0, 25.00/3.5  | 775 | 1752 | 787 | 5311 | TL   | 45          | 220  |
| 775/65 R 29                 | CUT RESISTANT COMPOUND | E3       | **     | 195 B        | 24.00/3.5  | 24.00/3.0, 25.00/3.5  | 775 | 1752 | 787 | 5311 | TL   | 45          | 220  |
| 775/65 R 29                 | CUT RESISTANT COMPOUND | L3       | *      | 206 A2       | 24.00/3.5  | 24.00/3.0, 25.00/3.5  | 775 | 1752 | 787 | 5311 | TL   | 45          |      |
| 775/65 R 29                 | CUT RESISTANT COMPOUND | L3       | **     | 213 A2       | 24.00/3.5  | 24.00/3.0, 25.00/3.5  | 775 | 1752 | 787 | 5311 | TL   | 45          |      |
| 875/65 R 29<br>(35/65 R 29) | CUT RESISTANT COMPOUND | L3       | *      | 214 A2       | 27.00/3.50 | 27.00/3.0, 28.00/3.5  | 890 | 1860 | 816 | 5559 | TL   | 48          |      |
| 875/65 R 29<br>(35/65 R 29) | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 203 B/214 A2 | 27.00/3.50 | 27.00/3.0, 28.00/3.5  | 890 | 1860 | 816 | 5559 | TL   | 48          | 279  |
| 875/65 R 29<br>(35/65 R 29) | CUT RESISTANT COMPOUND | E3       | **     | 203 B        | 27.00/3.50 | 27.00/3.0, 28.00/3.5  | 890 | 1860 | 816 | 5559 | TL   | 48          | 279  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 8:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..