

# EARTHMAX SR 41 - Especificaciones técnicas



## Description

EARTHMAX SR 41 es un neumático radial totalmente de acero perfecto para volquetes articulados, cargadoras y topadoras. Gracias a su estructura totalmente de acero y su patrón de bloques especial, EARTHMAX SR 41 ofrece una excelente resistencia a los pinchazos y una vida útil prolongada. Además de largas horas de trabajo sin tiempo de parada, el neumático garantiza una comodidad extraordinaria. EARTHMAX SR 41 también está disponible en SH-4\*\*\*\* para los volquetes de perfil bajo (LPDT) empleados en operaciones de transporte subterráneo.

## UM

US Standard

## Construction

 RADIAL

## Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora • Volquete de perfil bajo

Version	STANDARD COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B

## Dimensions US Standard

Usa code	94041527
TMPH	161
Overall Width (inch)	26.7
Overall Diameter (inch)	68.6
Static Loaded Radius (inch)	30.5
Rolling Circumference (inch)	202.8
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	E4
Tread Depth	74

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	20900	21500	22700	23400	24700	25400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 19:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..