

EARTHMAX SR 41 - Especificaciones técnicas



Description

EARTHMAX SR 41 es un neumático radial totalmente de acero perfecto para volquetes articulados, cargadoras y topadoras. Gracias a su estructura totalmente de acero y su patrón de bloques especial, EARTHMAX SR 41 ofrece una excelente resistencia a los pinchazos y una vida útil prolongada. Además de largas horas de trabajo sin tiempo de parada, el neumático garantiza una comodidad extraordinaria. EARTHMAX SR 41 también está disponible en SH-4**** para los volquetes de perfil bajo (LPDT) empleados en operaciones de transporte subterráneo.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora • Volquete de perfil bajo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	221 A2

Dimensions US Standard

Usa code	94070367
Overall Width (inch)	30
Overall Diameter (inch)	73.3
Static Loaded Radius (inch)	32.7
Rolling Circumference (inch)	216.9
Rim Rec	25.00/3.5
Star Rating	***
TRA Code	L4
Tread Depth	83

Load capacity (lbs)

mph / psi	98	102	105	109	112	116
5	50700	52000	53600	54700	55600	56800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 2:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..