

## EARTHMAX SR 42 - Especificaciones técnicas



### Description

EARTHMAX SR 42 es un neumático radial OTR particularmente proyectado para los trenes de carretera "haul train" que se utilizan en las minas y en las aplicaciones pesadas para el transporte de madera. El característico diseño de la banda de rodadura asegura una excelente tracción y estabilidad lateral, así como óptimas prestaciones de frenado y comportamiento en las curvas tanto en terrenos accidentados como en la grava, incluso con nieve y hielo. En efecto, la mezcla de la banda de rodadura, particularmente resistente a los cortes y al desgaste, es idónea en condiciones climáticas extremadamente frías. EARTHMAX SR 42 presenta una carcasa **All Steel** que garantiza una óptima duración y una larga vida operativa.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Haul Train

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 25
LI/SS	171 B

## Dimensions International Standard

TKPH	105
Overall Width (mm)	380
Overall Diameter (mm)	1412
Static Loaded Radius (mm)	652
Rolling Circumference (mm)	4231
Rim Rec	10.00/2.0
Rim Alt	--
Star Rating	***
TRA Code	E4
Tread Depth	38

## Load capacity (Kg)

km/h / bar	7.00	8.00
50	5800	6150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 14:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..