

EARTHMAX SR 44 - Especificaciones técnicas



Description

EARTHMAX SR 44 es un neumático radial **All Steel** idóneo para una amplia serie de aplicaciones, incluidas las realizadas en el sector minero, forestal y del transporte. El robusto dibujo de la banda de rodadura E-4 asegura una excelente tracción y confort para el operador. EARTHMAX SR 44 (E-4) puede optimizar la productividad, cualquiera que sea la operación que haya que realizar.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Volquete

Version	STANDARD
Type	TT
Tyre Size	12.00 R 24 (325/95 R 24)
LI/SS	158 B

Dimensions International Standard

TKPH	140
Overall Width (mm)	310
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	575
Rolling Circumference (mm)	3790
Rim Rec	8.50V
Rim Alt	9.00V
Star Rating	***
TRA Code	E4
Tread Depth	30

Load capacity (Kg)

km/h / bar	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	3075	3150	3350	3450	3550	3650	3750	3875	4000	4125	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 6:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..