

EARTHMAX SR 46 - Especificaciones técnicas



Description

Earthmax SR 46 para dumpers rígidos es la respuesta innovadora para los ambientes rocosos, abrasivos y hostiles de las minas. Este neumático ha sido particularmente proyectado para el transporte de cargas pesadas y ofrece una excepcional resistencia a los cortes y las laceraciones, así como un ciclo de vida más largo del producto. La carcasa y los cinturones **All Steel** aseguran una protección extraordinaria contra los golpes, las solicitaciones y los pinchazos, maximizando las horas operativas e incrementando la productividad. Earthmax SR 46 se caracteriza por un especial diseño de la banda de rodadura, provisto de tacos en bloques y ranura a lo largo de la circunferencia. Esto significa óptimas prestaciones en las curvas, con el mínimo daño a la parte exterior de la banda de rodadura.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dúmpster rígido

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	33.00 R 51
LI/SS	235 B

Dimensions International Standard

TKPH	800
Overall Width (mm)	905
Overall Diameter (mm)	3050
Static Loaded Radius (mm)	1401
Rolling Circumference (mm)	9377
Rim Rec	24.00/5.0
Star Rating	**
TRA Code	E4
Tread Depth	87

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	30000	30750	32500	33500	34500	35500	36500	37500	38750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/05/2025 9:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..