

EARTHMAX SR 46 - Ficha técnica



Description

Earthmax SR 46 para dumpers rígidos es la respuesta innovadora para los ambientes rocosos, abrasivos y hostiles de las minas. Este neumático ha sido particularmente proyectado para el transporte de cargas pesadas y ofrece una excepcional resistencia a los cortes y las laceraciones, así como un ciclo de vida más largo del producto. La carcasa y los cinturones **All Steel** aseguran una protección extraordinaria contra los golpes, las solicitaciones y los pinchazos, maximizando las horas operativas e incrementando la productividad. Earthmax SR 46 se caracteriza por un especial diseño de la banda de rodadura, provisto de tacos en bloques y ranura a lo largo de la circunferencia. Esto significa óptimas prestaciones en las curvas, con el mínimo daño a la parte exterior de la banda de rodadura.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Dúmpster rígido

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TKPH
27.00 R 49	CUT RESISTANT COMPOUND	E4	**	223 B	19.50/4.0	-	746	2688	1225	8165	TL	68	455
27.00 R 49	HEAT RESISTANT COMPOUND	E4	**	223 B	19.50/4.0	-	746	2688	1225	8165	TL	68	655
27.00 R 49	STANDARD COMPOUND	E4	**	223 B	19.50/4.0	-	746	2688	1225	8165	TL	68	590
30.00 R 51	CUT RESISTANT COMPOUND	E4	**	230 B	22.00/4.5		835	2895	1300	8800	TL	77	500
30.00 R 51	HEAT RESISTANT COMPOUND	E4	**	230 B	22.00/4.5		835	2895	1300	8800	TL	77	725
30.00 R 51	STANDARD COMPOUND	E4	**	230 B	22.00/4.5		835	2895	1300	8800	TL	77	610
33.00 R 51	CUT RESISTANT COMPOUND	E4	**	235 B	24.00/5.0		905	3050	1401	9377	TL	87	558
33.00 R 51	HEAT RESISTANT COMPOUND	E4	**	235 B	24.00/5.0		905	3050	1401	9377	TL	87	800
33.00 R 51	STANDARD COMPOUND	E4	**	235 B	24.00/5.0		905	3050	1401	9377	TL	87	697

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/05/2025 10:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..