

EARTHMAX SR 49 - Especificaciones técnicas



Description

EARTHMAX SR 49 (L-4) es un neumático radial All Steel proyectado para palas cargadoras, buldóceres, volquetes de perfil bajo y cargadoras LHD. EARTHMAX SR 49 asegura óptimas prestaciones en las difíciles operaciones que se realizan en las minas, donde su tracción y estabilidad excelentes son requisitos esenciales. El neumático se distingue por el dibujo direccional y la mezcla particularmente resistente a los cortes que ofrecen una larga durabilidad.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Buldócer • Cargadora LHD • Pala cargadora • Volquete de perfil bajo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	45/65 R 45
LI/SS	245 A2

Dimensions US Standard

Usa code	94067572
Overall Width (inch)	44.5
Overall Diameter (inch)	107.5
Static Loaded Radius (inch)	46.9
Rolling Circumference (inch)	319.4
Rim Rec	36.00/4.5
Star Rating	**
TRA Code	L4
Tread Depth	91

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	96500	99000	102000	104500	110000	113500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 8:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..