

EARTHMAX SR 50 - Especificaciones técnicas



Description

EARTHMAX SR 50 (L-5) es un neumático radial **All Steel** particularmente proyectado para cargadoras. Su resistente carcasa y los cordones de protección son ideales para las operaciones más exigentes. EARTHMAX SR 50 está realizado con una mezcla especialmente resistente a los cortes que reduce el desgaste y asegura un ciclo de vida más largo al neumático. Los operadores apreciarán también la excelente tracción, así como la estabilidad y una conducción más confortable.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	208 A2

Dimensions International Standard

Overall Width (mm)	775
Overall Diameter (mm)	1901
Static Loaded Radius (mm)	862
Rolling Circumference (mm)	5722
Rim Rec	25.00/3.5
Star Rating	*
TRA Code	L5
Tread Depth	96

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	15500	16000	17000	17500	18000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..