

EARTHMAX SR 53 - Especificaciones técnicas



Description

EARTHMAX SR 53 es un neumático radial All Steel particularmente proyectado para las cargadoras, las buldóceres y les volquetes de perfil bajo (LPDT) que operan en condiciones difíciles, incluidos los ambientes rocosos y las operaciones en las minas subterráneas y en los depósitos de chatarra. La banda de rodadura profunda L-5 y la mezcla particularmente resistente contra los cortes reducen notablemente el desgaste y aseguran tracción y estabilidad excelentes.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Buldócer • Pala cargadora • Volquete de perfil bajo

Version	CUT RESISTANT COMPOUND (UMS)
Type	TL
Tyre Size	29.5 R 29

Dimensions US Standard

Usa code	94069309
Overall Width (inch)	29.7
Overall Diameter (inch)	79.3
Static Loaded Radius (inch)	35.6
Rolling Circumference (inch)	238.5
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5
Star Rating	**
TRA Code	L5
Tread Depth	129

Load capacity (lbs)

mph / psi	-
-	-

* "In case of underground mine application, consult your servicing dealer or BKT representative."

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 4:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..