

EARTHMAX SR 55 - Especificaciones técnicas



Description

EARTHMAX SR 55 (L-55) es un neumático radial All Steel especialmente proyectado para las palas cargadoras, los buldóceres y las cargadoras que operan en condiciones muy difíciles, como en las canteras, las minas y en los depósitos de chatarra. Gracias al dibujo de la banda de rodadura extra profundo y liso, EARTHMAX SR 55 puede alcanzar elevados niveles de productividad con menores tiempos de parada de la máquina. Los operadores de las máquinas apreciarán también estabilidad y tracción extraordinarias.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Buldócer • Cargadora LHD • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	209 A2

Dimensions International Standard

Overall Width (mm)	690
Overall Diameter (mm)	1786
Static Loaded Radius (mm)	810
Rolling Circumference (mm)	5375
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	L5S
Tread Depth	95

Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	15500	16000	16500	17000	18000	18500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 16:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..