

EARTHMAX SR LOADER - Especificaciones técnicas



Description

EARTHMAX SR LOADER es un neumático OTR especialmente diseñado para operaciones de carga y nivelación, así como para aplicaciones de transporte con dúmpers articulados. Su carcasa All Steel, reforzada con cinturones de acero multicapa y la exclusiva mezcla de la banda de rodadura ofrecen una excepcional resistencia a los desgarros y los pinchazos, lo que se traduce en una prolongada vida útil del neumático. EARTHMAX SR LOADER está equipado con un exclusivo dibujo de la banda de rodadura que garantiza óptimas propiedades de autolimpieza y una excelente tracción en diferentes tipos de terreno.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/186 A2

Dimensions International Standard

TKPH	170
Overall Width (mm)	530
Overall Diameter (mm)	1475
Static Loaded Radius (mm)	649
Rolling Circumference (mm)	4384
Rim Rec	17.00/2.0
Star Rating	**/*
TRA Code	E3/L3
Tread Depth	29

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	5800	6150	6500	6700	6900	7300
10	8000	8250	8750	9000	9500	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 23:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..