

EM 936 SUPER - Especificaciones técnicas



Description

EM 936 SUPER ha sido particularmente desarrollado para excavadoras y manipuladores telescópicos en las operaciones de excavación y carga así como para aplicaciones de transporte. Gracias a su ancho de la banda de rodadura aumentado del 8-10%, EM 936 SUPER se distingue por una extraordinaria estabilidad y un excelente confort de conducción. Este neumático asegura también un elevado confort en el movimiento y suministra una excelente tracción, incluso en condiciones de servicios pesados.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Pala excavadora

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20
LI/SS	145 B

Dimensions International Standard

Ply Rating	14
Section Width (mm)	277
Overall Diameter (mm)	1080
Static Loaded Radius (mm)	500
Rolling Circumference (mm)	3336
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

Load capacity (Kg)

km/h / bar	6.50
50	2900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 14:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..