

EM 936 - Especificaciones técnicas



Description

EM 936 ha sido particularmente desarrollado para excavadoras, elevadores y manipuladores telescópicos en las operaciones de excavación y carga. Además, una de sus medidas es particularmente idónea para las motoniveladoras y las cargadoras utilizadas en las operaciones de nivelación, carga y transporte. EM 936 se caracteriza por el extraordinario confort de conducción y sus mejores propiedades de auto limpieza. Este neumático asegura también un elevado confort en el movimiento y suministra una excelente tracción, incluso en condiciones de trabajo difícil. Su versión "especial" ha sido realizada con una mezcla especial.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Pala excavadora • Elevador telescópico

Version	STANDARD
Type	TL
Tyre Size	28X9.00-15 (240/70 - 15)
LI/SS	102 A6

Dimensions International Standard

Ply Rating	6
Overall Width (mm)	236
Overall Diameter (mm)	750
Rim Rec	7.00 I
Rim Alt	6,5 K

Load capacity (Kg)

km/h / bar	2.50
30	850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 11:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..