

EM 937 E3 (L) - Ficha técnica



Description

EM 937 (E-3/L-3) ha sido particularmente proyectado para los dúmpers rígidos que se utilizan en las minas a cielo abierto. Este neumático ofrece una excelente durabilidad, así como una elevada resistencia a los cortes y los desgarros. EM 937 (E-3/L-3) es particularmente idóneo para las operaciones de trabajo más pesadas.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Cargadora retroexcavadora • Pala cargadora

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 24	STANDARD	E3/L3	20	10.00 W		375	1368	628	4050	TT
14.00 - 24	STANDARD	E3/L3	20	10.00 W		375	1368	628	4050	TL
14.00 - 24	STANDARD	E3/L3	24	10.00 W		375	1368	628	4050	TT
14.00 - 24	STANDARD	E3/L3	24	10.00 W		375	1368	628	4050	TL
14.00 - 24	STANDARD	E3/L3	28	10.00 W		375	1368	628	4050	TT
14.00 - 24	STANDARD	E3/L3	28	10.00 W		375	1368	628	4050	TL
14.00 - 24	STANDARD	E3/L3	32	10.00 W		375	1368	628	4050	TT
14.00 - 24	STANDARD	E3/L3	32	10.00 W		375	1368	628	4050	TL
14.00 - 25	ARAMID + STEEL BELTED	E3	20	10.00/1.5		375	1368	620	4105	TT
14.00 - 25	ARAMID BELTED	E3/L3	20	10.00/1.5		375	1368	620	4105	TT
14.00 - 25	STANDARD	E3/L3	12	10.00/1.5		390	1368	620	4105	TT
14.00 - 25	STANDARD	E3/L3	20	10.00/1.5		375	1368	620	4105	TT
14.00 - 25	STANDARD	E3/L3	20	10.00/1.5		375	1368	620	4105	TL
14.00 - 25	STANDARD	E3/L3	24	10.00/1.5		375	1368	620	4105	TT
14.00 - 25	STANDARD	E3/L3	24	10.00/1.5		375	1368	620	4105	TL
14.00 - 25	STEEL BELTED	E3/L3	20	10.00/1.5		375	1368	620	4105	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 3:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..