

EM 937 IND3 (ECH) - Especificaciones técnicas



Description

EM 937 (E-3) IND ha sido particularmente proyectado para la manipulación de contenedores vacíos en las aplicaciones de apilamiento y carga. Este neumático se caracteriza por una excelente durabilidad y un largo ciclo de vida. EM 937 (E-3) IND es ideal para las superficies pavimentadas y todas las operaciones que requieran un elevado nivel de manipulación en los puertos. *For size 14.00-24 please confirm service rim or consult manufacturer/distributor

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Manipulador de contenedores vacios

Version	PORT INDUSTRIAL
Type	TT
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	628
Rolling Circumference (mm)	4050
Rim Rec	10.00 W
TRA Code	IND3

Load capacity (Kg)

km/h / bar	10.00
10	14175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 22:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..