

EM 938 - Ficha técnica



Description

EM 938 ha sido específicamente proyectado para las excavadoras que se utilizan en la construcción de carreteras. Este neumático ha sido realizado con una mezcla especial de la banda de rodadura, particularmente resistente contra los cortes y los desgarros, mientras que el agresivo dibujo de la banda de rodadura asegura una excelente tracción. EM 938 se caracteriza por sus extraordinarias propiedades de auto limpieza. Su robusta carcasa proporciona una resistencia excepcional contra los golpes y las sacudidas, incluso en las operaciones de servicio más pesadas.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Pala excavadora

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	0	OD	SLR	RC	Type
9.00 - 20	STANDARD	E2		16	7.0	6.5 ; 7.5	256	1012	481	3070	TT
9.00 - 20	STANDARD	E2	140 B	14	7.0	6.5 ; 7.5	256	1012	481	3070	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 10:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..