

FARM SPECIAL - Especificaciones técnicas



Description

FARM SPECIAL es un neumático para tractores, idóneo tanto para los trabajos del campo. La carcasa robusta garantiza un elevado nivel de resistencia a los pinchazos y una vida operativa más larga, mientras que los hombros redondeados evitan daños al terreno, protegiendo los cultivos más delicados. FARM SPECIAL se caracteriza por su especial dibujo de la banda de rodadura con elementos mud breaker que rompen el fango, optimizando las propiedades de auto-limpieza. Además, la doble angulación de los tacos asegura una óptima tracción con un menor deslizamiento.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	13.6 - 24
LI/SS	123 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	350
Overall Diameter (mm)	1205
Static Loaded Radius (mm)	554
Rolling Circumference (mm)	3635
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-005530
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.00
30	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 15:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..